

Product data sheet https://autonoxfinder.com/en/AT 50030

Date of download: Oct 16, 2025 Time of download: 00:21 UTC

ARTICULATED articc5-2000-20kg

Article number: AT_50030

Lubricant variant: Synthetic lubricants



Description:

This type of robot is based on the principle of serial kinematics. All drives and motor cables are moved along. The robot has three (3) translational and two (2) rotational degrees of freedom.

Scope of delivery:

Robot mechanics incl. gearbox, Free installation of drive technology provided (including incoming goods inspection), Multi-hour, logged test run as final quality inspection, Threaded protection caps, Transport and packing instructions

Required accessories:

Set of parts for installing the drive technology. This set consists of, for example, a servo motor adapter, servo motor cable, transmission input pinion, plug board (usually on the base frame).



Product data sheet https://autonoxfinder.com/en/AT_50030

Date of download: Oct 16, 2025 Time of download: 00:21 UTC

Technical specifications:

Field of application	Standard (not hygienic)
Kinematics	Serial
Translatory Degrees of Freedom (X,Y,Z)	3
Rotational Degrees of Freedom (α,β,γ)	2
Nominal payload [kg lbs] *	20 44.1
Supplementary load on the arm [kg lbs]	10 22.0
Working area-reach [mm in]	2000 78.7
Lubricants of the bearings	Synthetic
Lubricants of the gearboxes	Synthetic
Cleaning	No high pressure
Protection class	IP64
Ambient temperature [°C °F]	0 to +40 +32 to +104
Relative humidity level [%]	95 (free of condensation)
Mounting position	Floor, Ceiling
Robot weight without drive engineering (esp. drive) [kg lbs]	128 282.2

^{*} All given values are nominal values (nominal payload referred to a nominal performance) and can vary under realworld conditions depending on the application (tool specifications, load distances, reduction (partly) of the nominal performance when using food-grade lubricants, ...). Please consider our technical data sheets regarding the load capacity.