

## Product data sheet <a href="https://autonoxfinder.com/en/A\_00705-FO">https://autonoxfinder.com/en/A\_00705-FO</a>

Date of download: Oct 16, 2025 Time of download: 21:38 UTC

### HHD DELTA RL3-1200-1kg

Article number: A\_00705-FO

Lubricant variant: Food-grade lubricants (FO)




#### **Description:**

This type of robot is based on the principle of parallel kinematics. All drives are mounted in a fixed position on the robot head. Motor cables are not moved. The robot has three (3) translational of freedom.

#### **Scope of delivery:**

Robot mechanics incl. gearbox, Servo motor adapter, Transport and packing instructions

#### **Connecting dimensions:**



<u>Downloads:</u> <u>Connecting dimensions (PDF)</u> <u>3D model (STP)</u> <u>3D model (PDF)</u>



# Product data sheet https://autonoxfinder.com/en/A\_00705-FO

Date of download: Oct 16, 2025 Time of download: 21:38 UTC

#### **Technical specifications:**

Field of application	Hygienic 'HHD'
Kinematics	Parallel
Translatory Degrees of Freedom (X,Y,Z)	3
Rotational Degrees of Freedom $(\alpha,B,\gamma)$	0
Nominal payload [kg lbs] *	1   2.2
Working area-diameter [mm in]	1200   47.2
Working height outside [mm in]	330   13.0
Working height center [mm in]	487   19.2
Bearing type of the arm joints	Roller bearing
Lubricants of the bearings	Food-grade (FO)
Lubricants of the gearboxes	Food-grade (FO)
Cleaning	Up to 28 bar   406 psi high pressure
Protection class	IP69K
Ambient temperature [°C °F]	0 to +40   +32 to +104
Relative humidity level [%]	95 (free of condensation)
Mounting position	Floor, Ceiling, Wall (on request), Angle (on request)

<sup>\*</sup> All given values are nominal values (nominal payload referred to a nominal performance) and can vary under realworld conditions depending on the application (tool specifications, load distances, reduction (partly) of the nominal performance when using food-grade lubricants, ...). Please consider our technical data sheets regarding the load capacity.