# DELTA RL3-1600-12kg




**Article number:** A_00826-01

**Lubricant variant:** Synthetic lubricants

**Description:**
This type of robot is based on the principle of parallel kinematics. All drives are mounted in a fixed position on the robot head. Motor cables are not moved. The robot has three (3) translational degrees of freedom.

**Scope of delivery:**
Robot mechanics incl. gearbox, Servo motor adapter, Threaded protection caps , Transport and packing instructions

**Connecting dimensions:**




**Downloads:** Connecting dimensions (PDF) 3D model (STP) 3D model (PDF)

**We refer to our General Terms of Sale and Supply and Terms of Use.**

© 2026 autonox Robotics GmbH | www.autonox.com

## Technical specifications:

| | |
|---|---|
| **Field of application** | Standard (not hygienic) |
| **Kinematics** | Parallel |
| **Translatory Degrees of Freedom (X,Y,Z)** | 3 |
| **Rotational Degrees of Freedom (α,ß,γ)** | 0 |
| **Nominal payload [kg\|lbs] *** | 12 \| 26.5 |
| **Working area-diameter [mm\|in]** | 1600 \| 63.0 |
| **Working height outside [mm\|in]** | 400 \| 15.7 |
| **Working height center [mm\|in]** | 620 \| 24.4 |
| **Bearing type of the arm joints** | Roller bearing |
| **Lubricants of the gearboxes** | Synthetic |
| **Cleaning** | No high pressure |
| **Ambient temperature [°C\|°F]** | 0 to +40 \| +32 to +104 |
| **Relative humidity level [%]** | 95 (free of condensation) |
| **Mounting position** | Floor, Ceiling, Wall (on request), Angle (on request) |

* All given values are nominal values (nominal payload referred to a nominal performance) and can vary under realworld conditions depending on the application (tool specifications, load distances, reduction (partly) of the nominal performance when using food-grade lubricants, ...). Please consider our technical data sheets regarding the load capacity.

**We refer to our General Terms of Sale and Supply and Terms of Use.**

© 2026 autonox Robotics GmbH | www.autonox.com