

## Product data sheet https://autonoxfinder.com/en/A\_00855-01-FO

Date of download: Oct 16, 2025 Time of download: 12:02 UTC

### **DELTA RL3-1600-6kg**

Article number: A\_00855-01-FO

**Lubricant variant:** Food-grade lubricants (FO)



#### Description:

This type of robot is based on the principle of parallel kinematics. All drives are mounted in a fixed position on the robot head. Motor cables are not moved. The robot has three (3) translational degrees of freedom.

#### Scope of delivery:

Robot mechanics incl. gearbox, Servo motor adapter, Threaded protection caps, Transport and packing instructions



# Product data sheet https://autonoxfinder.com/en/A\_00855-01-FO

Date of download: Oct 16, 2025 Time of download: 12:02 UTC

### **Technical specifications:**

Field of application	Standard (not hygienic)
Kinematics	Parallel
Translatory Degrees of Freedom (X,Y,Z)	3
Rotational Degrees of Freedom $(\alpha,\beta,\gamma)$	0
Nominal payload [kg lbs] *	6   13.2
Working area-diameter [mm in]	1600   63.0
Working height outside [mm in]	270   10.6
Working height center [mm in]	521   20.5
Bearing type of the arm joints	Roller bearing
Lubricants of the bearings	Food-grade (FO)
Lubricants of the gearboxes	Food-grade (FO)
Cleaning	No high pressure
Ambient temperature [°C °F]	0 to +40   +32 to +104
Relative humidity level [%]	95 (free of condensation)
Mounting position	Floor, Ceiling, Wall (on request), Angle (on request)

<sup>\*</sup> All given values are nominal values (nominal payload referred to a nominal performance) and can vary under realworld conditions depending on the application (tool specifications, load distances, reduction (partly) of the nominal performance when using food-grade lubricants, ...). Please consider our technical data sheets regarding the load capacity.