

## Product data sheet https://autonoxfinder.com/en/A 00883

Date of download: Dec 3, 2025 Time of download: 13:34 UTC

### DELTA RLT5-1074-3kg

Article number: A\_00883

Lubricant variant: Synthetic lubricants




#### **Description:**

This type of robot is based on the principle of parallel kinematics. All drives are mounted in a fixed position on the robot head. Motor cables are not moved. The robot has three (3) translational and two (2) rotational degrees of freedom. This mechanics is a special kinematic version, which is very demanding in terms of control. Please contact us directly if you are interested in using the mechanics.

#### Scope of delivery:

Robot mechanics incl. gearbox, Servo motor adapter, Threaded protection caps, Transport and packing instructions

#### **Connecting dimensions:**



<u>Downloads:</u> <u>Connecting dimensions (PDF)</u> <u>3D model (STP)</u> <u>3D model (PDF)</u>



# Product data sheet <a href="https://autonoxfinder.com/en/A\_00883">https://autonoxfinder.com/en/A\_00883</a>

Date of download: Dec 3, 2025 Time of download: 13:34 UTC

#### **Technical specifications:**

Field of application	Standard (not hygienic)
Kinematics	Parallel
Translatory Degrees of Freedom (X,Y,Z)	3
Rotational Degrees of Freedom $(\alpha,\beta,\gamma)$	2
Nominal payload [kg lbs] *	3   6.6
Working area-width X/Y [mm in]	1074/774   42.3/30.5
Working height outside [mm in]	500   19.7
Working height center [mm in]	575   22.6
Max. acceleration torque of the rotation $\alpha/\beta$ around X/Y at the output [Nm in.lbs]	16   141.6
Nominal torque of the rotation $\alpha/\beta$ around X/Y at the output [Nm   in.lbs]	16   141.6
Max. speed of the rotation $\alpha/\beta$ around X/Y at the output [1/min]	82
Nominal speed of the rotation $\alpha/\beta$ around X/Y at the output [1/min]	82
Max. acceleration torque of the rotation y around Z at the output [Nm in.lbs]	40   354.0
Nominal torque of the rotation y around Z at the output [Nm in.lbs]	40   354.0
Max. speed of the rotation y around Z at the output [1/min]	260
Nominal speed of the rotation y around Z at the output [1/min]	160
Bearing type of the telescopic shaft(s)	Roller bearing
Bearing type of the arm joints	Roller bearing
Lubricants of the bearings	Synthetic
Lubricants of the gearboxes	Synthetic
Cleaning	No high pressure
Ambient temperature [°C °F]	0 to +40   +32 to +104
Relative humidity level [%]	95 (free of condensation)
Mounting position	Floor, Ceiling, Wall (on request), Angle (on request)
Special features	This mechanics is a special kinematic version, which is very demanding in terms of control. Please contact us directly if you are interested in using the mechanics.

<sup>\*</sup> All given values are nominal values (nominal payload referred to a nominal performance) and can vary under realworld conditions depending on the application (tool specifications, load distances, reduction (partly) of the nominal performance when using food-grade lubricants, ...). Please consider our technical data sheets regarding the load capacity.

#### **Gearbox article number for this robot mechanics:**

Function	Article number	Document
Drive of the upper arms	MT_BGR00020873-xx	Operating manual gearbox type 4 (PDF)
Drive of the telescopic shaft for rotation y around Z	MT_WST00064258-xx	Operating manual gearbox type 7 (PDF)

We refer to our **General Terms of Sale and Supply** and **Terms of use**.