



## Technical specifications:

Field of application	Standard (not hygienic)
Kinematics	Parallel
Translatory Degrees of Freedom (X,Y,Z)	3
Rotational Degrees of Freedom ( $\alpha, \beta, \gamma$ )	1
Nominal payload [kg   lbs] *	3   6.6
Working area-width X/Y [mm   in]	750/600   29.5/23.6
Working height outside [mm   in]	140   5.5
Working height center [mm   in]	282   11.1
Max. acceleration torque of the rotation $\beta$ around Y at the output [Nm   in.lbs]	16   141.6
Nominal torque of the rotation $\beta$ around Y at the output [Nm   in.lbs]	16   141.6
Max. speed of the rotation $\beta$ around Y at the output [1/min]	82
Nominal speed of the rotation $\beta$ around Y at the output [1/min]	82
Bearing type of the telescopic shaft(s)	Roller bearing
Bearing type of the arm joints	Roller bearing
Lubricants of the bearings	Food-grade (FO)
Lubricants of the gearboxes	Food-grade (FO)
Cleaning	No high pressure
Ambient temperature [°C   °F]	0 to +40   +32 to +104
Relative humidity level [%]	95 (free of condensation)
Mounting position	Floor, Ceiling, Wall (on request), Angle (on request)

\* All given values are nominal values (nominal payload referred to a nominal performance) and can vary under realworld conditions depending on the application (tool specifications, load distances, reduction (partly) of the nominal performance when using food-grade lubricants, ...). Please consider our technical data sheets regarding the load capacity.

## Gearbox article number for this robot mechanics:

Function	Article number	Document
Drive of the upper arms	MT_BGR00015703-xx-FO	Operating manual gearbox type 3 (PDF)