



## Technical specifications:

Field of application	Standard (not hygienic)
Kinematics	Parallel
Translatory Degrees of Freedom (X,Y,Z)	2
Rotational Degrees of Freedom ( $\alpha, \beta, \gamma$ )	1
Nominal payload [kg   lbs] *	3   6.6
Working area-width [mm   in]	750   29.5
Working height outside [mm   in]	275   10.8
Working height center [mm   in]	415   16.3
Output type of the tool actuation	Flange (T)
Number of the tool actuation (telescopic shaft(s))	1
Max. acceleration torque of the rotation $\beta$ around Y at the output [Nm   in.lbs]	16   141.6
Nominal torque of the rotation $\beta$ around Y at the output [Nm   in.lbs]	16   141.6
Max. speed of the rotation $\beta$ around Y at the output [1/min]	82
Nominal speed of the rotation $\beta$ around Y at the output [1/min]	82
Max. acceleration torque of the tool actuation T/TS1 at the output [Nm   in.lbs]	13,3   117.7
Nominal torque of the tool actuation T/TS1 at the output [Nm   in.lbs]	13,3   117.7
Max. speed of the tool actuation T/TS1 at the output [1/min]	228
Nominal speed of the tool actuation T/TS1 at the output [1/min]	228
Bearing type of the telescopic shaft(s)	Roller bearing
Bearing type of the arm joints	Roller bearing
Lubricants of the bearings	Food-grade (FO)
Lubricants of the gearboxes	Food-grade (FO)
Cleaning	No high pressure
Ambient temperature [°C   °F]	0 to +40   +32 to +104
Relative humidity level [%]	95 (free of condensation)
Mounting position	Floor, Ceiling, Wall (on request), Angle (on request)
Robot weight without drive engineering (esp. drive) [kg   lbs]	57   125.7

\* All given values are nominal values (nominal payload referred to a nominal performance) and can vary under realworld conditions depending on the application (tool specifications, load distances, reduction (partly) of the nominal performance when using food-grade lubricants, ...). Please consider our technical data sheets regarding the load capacity.