
# DuoPod RVS3Y-1000-6kg




**Article number:** A_00906-FO

**Lubricant variant:** Food-grade lubricants (FO)

**Description:**
This type of robot is based on the principle of parallel kinematics. All drives are mounted in a fixed position on the robot head. Motor cables are not moved. The robot has two (2) translational and one (1) rotational degree(s) of freedom.

**Scope of delivery:**
Robot mechanics incl. gearbox, Servo motor adapter, Threaded protection caps , Transport and packing instructions

**Connecting dimensions:**




**Downloads:** Connecting dimensions (PDF) 3D model (STP) 3D model (PDF)

**We refer to our General Terms of Sale and Supply and Terms of Use.**

© 2026 autonox Robotics GmbH | www.autonox.com

## Technical specifications:

| | |
|---|---|
| **Field of application** | Standard (not hygienic) |
| **Kinematics** | Parallel |
| **Translatory Degrees of Freedom (X,Y,Z)** | 2 |
| **Rotational Degrees of Freedom (α,ß,γ)** | 1 |
| **Nominal payload [kg\|lbs] *** | 6 \| 13.2 |
| **Working area-width [mm\|in]** | 1000 \| 39.4 |
| **Working height outside [mm\|in]** | 300 \| 11.8 |
| **Working height center [mm\|in]** | 435 \| 17.1 |
| **Max. acceleration torque of the rotation β around Y at the output [Nm\|in.lbs]** | 135 \| 1194.9 |
| **Nominal torque of the rotation β around Y at the output [Nm\|in.lbs]** | 135 \| 1194.9 |
| **Max. speed of the rotation β around Y at the output [1/min]** | 77 |
| **Nominal speed of the rotation β around Y at the output [1/min]** | 77 |
| **Bearing type of the telescopic shaft(s)** | Roller bearing |
| **Bearing type of the arm joints** | Roller bearing |
| **Lubricants of the bearings** | Food-grade (FO) |
| **Lubricants of the gearboxes** | Food-grade (FO) |
| **Cleaning** | No high pressure |
| **Ambient temperature [°C\|°F]** | 0 to +40 \| +32 to +104 |
| **Relative humidity level [%]** | 95 (free of condensation) |
| **Mounting position** | Floor, Ceiling, Wall (on request), Angle (on request) |
| **Robot weight without drive engineering (esp. motors) [kg\|lbs]** | 64 \| 141.1 |

* All given values are nominal values (nominal payload referred to a nominal performance) and can vary under realworld conditions depending on the application (tool specifications, load distances, reduction (partly) of the nominal performance when using food-grade lubricants, ...). Please consider our technical data sheets regarding the load capacity.

**We refer to our General Terms of Sale and Supply and Terms of Use.**

© 2026 autonox Robotics GmbH | www.autonox.com