



## Technical specifications:

<b>Field of application</b>	Standard (not hygienic)
<b>Kinematics</b>	Parallel
<b>Translatory Degrees of Freedom (X,Y,Z)</b>	2
<b>Rotational Degrees of Freedom (<math>\alpha,\beta,\gamma</math>)</b>	1
<b>Nominal payload [kg lbs] *</b>	3   6.6
<b>Working area-width [mm in]</b>	600   23.6
<b>Working height outside [mm in]</b>	335   13.2
<b>Working height center [mm in]</b>	415   16.3
<b>Max. acceleration torque of the rotation <math>\alpha</math> around X at the output [Nm in.lbs]</b>	16   141.6
<b>Nominal torque of the rotation <math>\alpha</math> around X at the output [Nm in.lbs]</b>	16   141.6
<b>Max. speed of the rotation <math>\alpha</math> around X at the output [1/min]</b>	82
<b>Nominal speed of the rotation <math>\alpha</math> around X at the output [1/min]</b>	82
<b>Bearing type of the telescopic shaft(s)</b>	Roller bearing
<b>Bearing type of the arm joints</b>	Roller bearing
<b>Lubricants of the bearings</b>	Food-grade (FO)
<b>Lubricants of the gearboxes</b>	Food-grade (FO)
<b>Cleaning</b>	No high pressure
<b>Ambient temperature [°C °F]</b>	0 to +40   +32 to +104
<b>Relative humidity level [%]</b>	95 (free of condensation)
<b>Mounting position</b>	Floor, Ceiling, Wall (on request), Angle (on request)

\* All given values are nominal values (nominal payload referred to a nominal performance) and can vary under realworld conditions depending on the application (tool specifications, load distances, reduction (partly) of the nominal performance when using food-grade lubricants, ...). Please consider our technical data sheets regarding the load capacity.