

## Product data sheet https://autonoxfinder.com/en/A 00925

Date of download: Nov 4, 2025 Time of download: 08:24 UTC

### DuoPod RVS3X-600-3kg

Article number: A\_00925

Lubricant variant: Synthetic lubricants




#### **Description:**

This type of robot is based on the principle of parallel kinematics. All drives are mounted in a fixed position on the robot head. Motor cables are not moved. The robot has two (2) translational and one (1) rotational degree(s) of freedom.

#### **Scope of delivery:**

Robot mechanics incl. gearbox, Servo motor adapter, Threaded protection caps, Transport and packing instructions

#### **Connecting dimensions:**



<u>Downloads:</u> <u>Connecting dimensions (PDF)</u> <u>3D model (STP)</u> <u>3D model (PDF)</u>



# Product data sheet <a href="https://autonoxfinder.com/en/A 00925">https://autonoxfinder.com/en/A 00925</a>

Date of download: Nov 4, 2025 Time of download: 08:24 UTC

#### **Technical specifications:**

Field of application	Standard (not hygienic)
Kinematics	Parallel
Translatory Degrees of Freedom (X,Y,Z)	2
Rotational Degrees of Freedom $(\alpha,\beta,\gamma)$	1
Nominal payload [kg lbs] *	3   6.6
Working area-width [mm in]	600   23.6
Working height outside [mm in]	335   13.2
Working height center [mm in]	415   16.3
Max. acceleration torque of the rotation $\alpha$ around X at the output [Nm $\mid$ in.lbs]	16   141.6
Nominal torque of the rotation $\alpha$ around X at the output [Nm $\mid$ in.lbs]	16   141.6
Max. speed of the rotation $\alpha$ around X at the output [1/min]	82
Nominal speed of the rotation $\boldsymbol{\alpha}$ around $\boldsymbol{X}$ at the output [1/min]	82
Bearing type of the telescopic shaft(s)	Roller bearing
Bearing type of the arm joints	Roller bearing
Lubricants of the bearings	Synthetic
Lubricants of the gearboxes	Synthetic
Cleaning	No high pressure
Ambient temperature [°C °F]	0 to +40   +32 to +104
Relative humidity level [%]	95 (free of condensation)
Mounting position	Floor, Ceiling, Wall (on request), Angle (on request)

<sup>\*</sup> All given values are nominal values (nominal payload referred to a nominal performance) and can vary under realworld conditions depending on the application (tool specifications, load distances, reduction (partly) of the nominal performance when using food-grade lubricants, ...). Please consider our technical data sheets regarding the load capacity.