

## ARTICULATED articc4-1839-45kg

Article number: AT\_40010



### **Description :**

This type of robot is based on the principle of serial kinematics. All drives and motor cables, except the stationary axis 1, are moved along. The robot has two (2) translational and two (2) rotational degree(s) of freedom.

### **Scope of delivery:**

Robot mechanics incl. gearbox, Free installation of drive technology provided (including incoming goods inspection), Multi-hour, logged test run as final quality inspection, Threaded protection caps , Transport and packing instructions

### **Required accessories:**

Set of parts for installing the drive technology. This set consists of, for example, a servo motor adapter, servo motor cable, transmission input pinion, plug board (usually on the base frame).

We refer to our [General Terms of Sale and Supply](#), [Terms of use](#) and [Disclaimer and Copyright notices](#).

## Technical specifications:

|                                                           |                                       |
|-----------------------------------------------------------|---------------------------------------|
| Field of application                                      | Standard (not hygienic), CNC Robotics |
| Kinematics                                                | Serial                                |
| Translatory Degrees of Freedom (X,Y,Z)                    | 2                                     |
| Rotational Degrees of Freedom ( $\alpha, \beta, \gamma$ ) | 2                                     |
| Nominal payload [kg   lbs] *                              | 45   99.2                             |
| Supplementary load on the arm [kg   lbs]                  | 40   88.2                             |
| Working area-reach [mm   in]                              | 1839   72.4                           |
| Lubricants of the bearings                                | Synthetic                             |
| Lubricants of the gearboxes                               | Synthetic                             |
| Cleaning                                                  | No high pressure                      |
| Protection class                                          | IP64                                  |
| Ambient temperature [°C   °F]                             | 0 to +40   +32 to +104                |
| Relative humidity level [%]                               | 95 (free of condensation)             |
| Mounting position                                         | Floor, Ceiling, Wall, Angle           |

\* All given values are nominal values (nominal payload referred to a nominal performance) and can vary under realworld conditions depending on the application (tool specifications, load distances, reduction (partly) of the nominal performance when using food-grade lubricants, ...). Please consider our technical data sheets regarding the load capacity.